

# RUDY-ADCA-3C



IS 10322(PART 5/SEC 1):2012  
R-71007862

Wattage: 23W | 27W


## PRODUCT HIGHLIGHTS

- Aesthetically designed compact power track mounted-accent luminaire
- Specially engineered 355° rotatable luminaire and 45°-90° adjustable light head
- The complete luminaire is made of die-cast aluminium
- High efficient passive cooling die-cast aluminium light head with rotatable arm
- Aesthetically designed anti glare ABS front ring
- High efficiency vacuum metalized polycarbonate reflector with beam angle options of 12°, 24°, 40° & 60°
- High efficacy chip on board (COB) LED technology
- Adaptor based inbuilt high efficiency electronic driver technology
- Adaptor-suitable for 3 wire / 4 wire power track
- Shade : powder coated - white, black & grey

3 CKT

## LED PARAMETERS

| WATTS | CRI | COLOR TEMP.            | LUMEN                     | CRI | COLOR TEMP. | LUMEN   |
|-------|-----|------------------------|---------------------------|-----|-------------|---------|
| 23W   | 90  | 3000 K, 3500 K, 4000 K | 2421 lm, 2467 lm, 2514 lm | 80  | 5700 K      | 2884 lm |
| 27W   |     | 3000 K, 3500 K, 4000 K | 2850 lm, 2858 lm, 2866 lm |     | 5700 K      | 3354 lm |




Application area for retail space:  
Focal area | Ambient | Show Window | Wall Display

# RUDY-ADCA-4C

GARDLER®



IS 10322(PART 5/SEC 1):2012  
R-71007862



Power Track-ACCENT LIGHT

Wattage: 19W | 23W | 25W | 27W | 29W


## TECHNICAL SPECIFICATIONS

Light Source : COB-Chip on Board  
Power Consumption : 19W, 23W, 25W, 27W, 29W

90 CRI : 3000 K | 3500 K | 4000 K  
80 CRI : 5700 K

Driver : Constant current AC-DC  
Input Voltage Range : 220-240 V  
Output Voltage : 33V-37V DC  
Output Current : 500 mA, 600 mA, 650 mA, 700 mA, 750 mA

Power Factor : >0.95  
THD : <15%



All dimensions are in mm

4 CKT

| WATTS | CRI | COLOR TEMP.            | LUMEN                     | CRI | COLOR TEMP. | LUMEN   |
|-------|-----|------------------------|---------------------------|-----|-------------|---------|
| 19W   | 90  | 3000 K, 3500 K, 4000 K | 2146 lm, 2149 lm, 2155 lm | 80  | 5700 K      | 2507 lm |
| 23W   |     | 3000 K, 3500 K, 4000 K | 2421 lm, 2467 lm, 2514 lm |     | 5700 K      | 2884 lm |
| 25W   |     | 3000 K, 3500 K, 4000 K | 2594lm, 2625 lm, 2664 lm  |     | 5700 K      | 3111 lm |
| 27W   |     | 3000 K, 3500 K, 4000 K | 2850lm, 2858 lm, 2866 lm  |     | 5700 K      | 3354 lm |
| 29W   |     | 3000 K, 3500 K, 4000 K | 2974lm, 2998 lm, 3036 lm  |     | 5700 K      | 3533 lm |