

• Recess mount - Down light



90 CRI

PRODUCT HIGHLIGHTS


- Aesthetically designed high performance recess down light luminaire
- The complete luminaire is made of die cast aluminium
- High efficient passive cooling die-cast aluminium heat sink housing
- High efficiency vacuum metalized polycarbonate reflector with beam angle options of 12°, 24°, 36° & 60°
- High efficacy chip on board (COB) LED technology
- Isolated-high efficiency electronic driver technology
- Heavy gauge spring toggle for easy installation on false ceiling application
- Shade : powder coated-white, black & grey

Available Colours



White Black Grey

Available Reflector Deg.



IP 20

12°


24°

36°

60°

TECHNICAL SPECIFICATIONS

Light Source	: COB - Chip on Board
Power Consumption	: 20w, 23w, 27w
Color Temperature	: 3000 K 3500 K 4000 K
Lumens	20w : 1875 lm, 1890 lm, 1930 lm 23w : 2160 lm, 2207 lm, 2219 lm 27w : 2480 lm, 2496 lm, 2529 lm
Driver	: Constant current AC - DC
Input voltage range	: 220 - 240 V
Output voltage	: 33V - 37V DC
Output Current	: 500 mA 600 mA 700 mA
Power Factor	: >0.98
THD	: <10%



Cut Dia. Ø96 mm

All dimensions are in mm

Product Application :

Retail Space | Ambient | Cash Counter | Trial Room