



Available Reflector Deg.



Recess-DOWN LIGHT

Wattage: 22W | 24W | 27W | 29W | 31W | 35W

TECHNICAL SPECIFICATIONS


Light Source	: COB-Chip on Board
Power Consumption	: 22W, 24W, 27W, 29W, 31W, 35W
90 CRI	: 3000 K 3500 K 4000 K
80 CRI	: 5700 K
Driver	: Constant Current AC-DC
Input Voltage Range	: 220-240 V
Output Voltage	: 33V-37V DC
Output Current	: 600 mA, 650 mA, 700 mA, 750 mA, 800mA, 900 mA
Power Factor	: >0.98
THD	: <10%

PRODUCT HIGHLIGHTS

- Aesthetically designed high performance recess asymmetric down light luminaire
- The luminaire housing is made of CRCA sheet steel with die-cast aluminium ring
- High efficient passive cooling-extruded aluminium heat sink
- High efficiency vacuum metalized polycarbonate asymmetric reflector for wall washer application
- High efficacy chip on board (COB) LED technology
- Isolated - high efficiency electronic driver technology
- Heavy gauge spring toggle for easy installation on false ceiling application
- Shade : powder coated - white, black & grey

LED PARAMETERS

WATTS	CRI	COLOR TEMP.	LUMEN	CRI	COLOR TEMP.	LUMEN
22W	90	3000 K, 3500 K, 4000 K	2166 lm, 2203 lm, 2308 lm	80	5700 K	2654 lm
24W		3000 K, 3500 K, 4000 K	2369 lm, 2413 lm, 2504 lm		5700 K	2806 lm
27W		3000 K, 3500 K, 4000 K	2534 lm, 2634 lm, 2722 lm		5700 K	3055 lm
29W		3000 K, 3500 K, 4000 K	2865 lm, 2976 lm, 2949 lm		5700 K	3287 lm
31W		3000 K, 3500 K, 4000 K	3091 lm, 3215 lm, 3279 lm		5700 K	3573 lm
35W		3000 K, 3500 K, 4000 K	3427 lm, 3561 lm, 3660 lm		5700 K	3912 lm



Cut Dia. Ø130 mm

All dimensions are in mm

Color choice



Application area for retail space:
Ambient | Entrance | Cash Counter | Trial Room