



IS 10322(PART 5/SEC 2):2012
R-71012963



Recess-ADJUSTABLE SPOT LIGHT


Wattage: 29W | 31W | 35W | 37W

TECHNICAL SPECIFICATIONS

Light source	: COB-Chip on Board
Power Consumption	: 29W, 31W, 35W, 37W
90 CRI	: 3000 K 3500 K 4000 K
80 CRI	: 5700 K
Driver	: Constant Current AC-DC
Input Voltage Range	: 220-240 V
Output Voltage	: 33V-37V DC
Output Current	: 750 mA, 800 mA, 900 mA, 950 mA
Power Factor	: >0.98
THD	: <10%

PRODUCT HIGHLIGHTS

- Aesthetically designed high performance tiltable recess-spot light luminaire
- The complete luminaire is made of die cast aluminium
- High efficient passive cooling die-cast aluminium heat sink housing
- The light head rotatable 350° and tiltable 35°
- Aesthetically designed anti glare die-cast aluminium front ring
- High efficiency vacuum metalized polycarbonate reflector with beam angle options of 12°, 24°, 45° & 60°
- High efficacy chip on board (COB) LED technology
- Isolated - high efficiency electronic driver technology
- Heavy gauge spring toggle for easy installation on false ceiling application
- Shade: powder coated-white, black & grey




LED PARAMETERS

WATTS	CRI	COLOR TEMP.	LUMEN	CRI	COLOR TEMP.	LUMEN
29W	90	3000 K, 3500 K, 4000 K	2867 lm, 2951 lm, 2997 lm	80	5700 K	3265 lm
31W		3000 K, 3500 K, 4000 K	3030 lm, 3114 lm, 3266 lm		5700 K	3496 lm
35W		3000 K, 3500 K, 4000 K	3343 lm, 3445 lm, 3573 lm		5700 K	3875 lm
37W		3000 K, 3500 K, 4000 K	3497 lm, 3602 lm, 3710 lm		5700 K	4090 lm

Cut Dia. Ø145 mm

Color choice



Driver options



All dimensions are in mm

Application area for retail space:
Focal area | Peripheral | Show Window | Wall Display