

MARLA-L-PM

GARDLER®



Pendant-DOWN LIGHT

Wattage : 31W | 35W


TECHNICAL SPECIFICATIONS

Light Source	: COB-Chip on Board
Power Consumption	: 31W, 35W
90 CRI	: 3000 K 3500 K 4000 K
80 CRI	: 5700 K
Driver	: Constant Current AC-DC
Input Voltage Range	: 220-240 V
Output Voltage	: 33V-37V DC
Output Current	: 800 mA, 900 mA
Power Factor	: >0.98
THD	: <10%

PRODUCT HIGHLIGHTS

- Aesthetically designed high performance pendant down light luminaire
- The complete luminaire is made of die-cast aluminium
- High efficient passive cooling die-cast aluminium heat sink housing
- Aesthetically designed anti glare ABS front ring
- High efficiency vacuum metalized polycarbonate reflector with beam angle options of 12°, 24°, 45° & 60°
- High efficacy chip on board (COB) LED technology
- Isolated-high efficiency electronic driver technology
- Shade: powder coated white, black & grey


All dimensions are in mm



LED PARAMETERS

WATTS	CRI	COLOR TEMP.	LUMEN	CRI	COLOR TEMP.	LUMEN
31W	90	3000 K, 3500 K, 4000 K	3044 lm, 3165 lm, 3224 lm	80	5700 K	3519 lm
35W		3000 K, 3500 K, 4000 K	3387 lm, 3496 lm, 3545 lm		5700 K	3852 lm

Color choice



Driver options



Application area for retail space:
Retail Space | Ambient | Cash Counter