



Recess-ADJUSTABLE SPOT LIGHT


Wattage: 1X29W | 1X31W | 1X35W | 1X37W

## TECHNICAL SPECIFICATIONS

Light source : COB-Chip on Board  
 Power Consumption : 1X29W, 1X31W, 1X35W, 1X37W  
 90 CRI : 3000 K | 3500 K | 4000 K  
 80 CRI : 5700 K  
 Driver : Constant Current AC-DC  
 Input Voltage Range : 220-240 V  
 Output Voltage : 33V-37V DC  
 Output Current : 750 mA, 800 mA, 900 mA, 950 mA  
 Power Factor : >0.98  
 THD : <10%

## PRODUCT HIGHLIGHTS

- Aesthetically & functionally designed high performance recess gimbal down light luminaire
- The complete luminaire housing is made of CRCA sheet steel
- High efficient passive cooling die-cast aluminium light head
- The light head individually fixed with gimbal ring to rotate 350° and tiltable 35°
- Aesthetically designed anti glare die-cast aluminium front ring
- High efficiency vacuum metalized polycarbonate reflector with beam angle options of 12°, 24°, 45° & 60°
- High efficacy chip on board (COB) LED technology
- Isolated-high efficiency electronic driver technology
- Heavy gauge clamp adjustment locking for easy installation on false ceiling application
- Shade : powder coated-white, black & grey





## LED PARAMETERS

WATTS	CRI	COLOR TEMP.	LUMEN	CRI	COLOR TEMP.	LUMEN
1X29W	90	3000 K, 3500 K, 4000 K	2867 lm, 2951 lm, 2997 lm	80	5700 K	3265 lm
1X31W		3000 K, 3500 K, 4000 K	3030 lm, 3114 lm, 3266 lm		5700 K	3496 lm
1X35W		3000 K, 3500 K, 4000 K	3343 lm, 3445 lm, 3573 lm		5700 K	3875 lm
1X37W		3000 K, 3500 K, 4000 K	3497 lm, 3602 lm, 3710 lm		5700 K	4090 lm

Cut Sq. 148X148 mm

Color choice



Driver options



Application area for retail space:

Focal area | Peripheral | Show Window | Wall Display