

• Surface - Diffuser Down light




80 CRI

PRODUCT HIGHLIGHTS


- Aesthetically designed high performance square surface down light luminaire
- The complete luminaire is made of die cast aluminium
- Highly efficient passive cooling die-cast aluminium heat sink housing
- High efficiency polycarbonate symmetric light distribution diffuser
- High efficacy SMD (Mid Powder) led mounted on MCPCB for better thermal performance
- Inbuilt-high efficiency electronic driver with suitable electrical connector
- Surface installation with ceiling clamp and accessories
- Shade : powder coated - white, black

Available Colours



TECHNICAL SPECIFICATIONS

Light Source	: MPL - Mid Power Led
Power Consumption	: 15W, 20W, 24W
Color Temperature	: 3000 K 4000 K 6500 K
Lumens	15W : 1309 lm, 1333 lm, 1386 lm 20W : 1665 lm, 1724 lm, 1825 lm 24W : 1923 lm, 2066 lm, 2420 lm
Driver	: Constant current AC - DC
Input voltage range	: 110 - 270 V
Output voltage	: 24V - 36V DC
Output Current	: 250 mA 275 mA 300 mA
Power Factor	: >0.98
THD	: <15%



All dimensions are in mm

Product Application :
Retail Space | Ambient | Trial Room | Stair case