



Pendant **HIGH-BAY DOWN LIGHT**


**Wattage: 40W | 60W**

## TECHNICAL SPECIFICATIONS


- Light source : MPL-Mid Power LED
- Power consumption : 40W, 60W
- Color temperature : 4000 K | 6500 K
- Driver : Constant Current AC-DC
- Input voltage range : 220-240 V
- Output voltage : 33V-39V DC
- Output current : 1000 mA, 1500 mA,
- Power factor : >0.95
- THD : <10%

## PRODUCT HIGHLIGHTS

- Surface / Pendant moisture proof IP65 luminaire
- Consist of polycarbonate housing with PMMA top diffuser
- High efficacy SMD LED - >140 lm/W LED and good colour rendering
- High efficiency electronic in-built driver
- Internal powder coated reflector and driver try



**40W**




**60W**

## LED KEY ASPECTS

WATTS	CRI	COLOR TEMP.	LUMEN	CRI	COLOR TEMP.	LUMEN
40W	90	3000 K, 3500 K, 4000 K	3760 lm 3840 lm 4040 lm	80	5700 K	4320 lm
60W		3000 K, 3500 K, 4000 K	5460 lm 5610 lm 5940 lm		5700 K	6360 lm

All dimensions are in mm



White CRI IP65 COB

**Product Application :** Factory | Warehouse