



IS 10322(PART 5/SEC 2):2012
R-71012963



Recess-ADJUSTABLE SPOT LIGHT


Wattage: 3X20W | 3X24W | 3X27W | 3X29W | 3X31W | 3X35W

TECHNICAL SPECIFICATIONS

Light source : COB-Chip on Board
 Power Consumption : 3X20W, 3X24W, 3X27W, 3X29W,
 3X31W, 3X35W
 90 CRI : 3000 K | 3500 K | 4000 K
 80 CRI : 5700 K
 Driver : Constant Current AC-DC
 Input Voltage Range : 220-240 V
 Output Voltage : 33V-37V DC
 Output Current : 600 mA, 650 mA, 700 mA
 750 mA, 800 mA, 900 mA
 Power Factor : >0.98
 THD : <10%

PRODUCT HIGHLIGHTS

- Aesthetically designed high performance recess adjustable accent luminaire
- The complete luminaire housing is made of CRCA frame and die cast aluminium infill and light head
- High efficiency vacuum metalized polycarbonate reflector with beam angle options of 12°, 24°, 45° & 60°
- High efficacy chip on board (COB) LED technology
- Isolated-high efficiency electronic driver technology
- Heavy gauge spring toggle for easy installation on false ceiling application
- Shade: powder coated-white, black & grey





LED PARAMETERS

WATTS	CRI	COLOR TEMP.	LUMEN	CRI	COLOR TEMP.	LUMEN
3X20W	90	3000 K, 3500 K, 4000 K	2214 lm, 2334 lm, 2369 lm	80	5700 K	2551 lm
3X24W		3000 K, 3500 K, 4000 K	2391 lm, 2513 lm, 2562 lm		5700 K	2756 lm
3X27W		3000 K, 3500 K, 4000 K	2686 lm, 2783 lm, 2789 lm		5700 K	2979 lm
3X29W		3000 K, 3500 K, 4000 K	2887 lm, 2934 lm, 3045 lm		5700 K	3192 lm
3X31W		3000 K, 3500 K, 4000 K	3037 lm, 3084 lm, 3144 lm		5700 K	3385 lm
3X35W		3000 K, 3500 K, 4000 K	3412 lm, 3474 lm, 3528 lm		5700 K	3794 lm

Cut Sq. 165X445 mm

Color choice



Driver options



All dimensions are in mm

Application area for retail space:
 Focal area | Peripheral | Show Window | Wall Display