

BARON-P

GARDLER®



Pendant-DOWN LIGHT

Wattage: 22W | 24W | 27W | 29W | 31W | 35W

TECHNICAL SPECIFICATIONS

Light Source	: COB-Chip on Board
Power Consumption	: 22W, 24W, 27W, 29W, 31W, 35W
90 CRI	: 3000 K 3500 K 4000 K
80 CRI	: 5700 K
Driver	: Constant Current AC-DC
Input Voltage Range	: 220-240 V
Output Voltage	: 33V-37V DC
Output Current	: 600 mA, 650 mA, 700 mA, 750mA, 800 mA, 900 mA
Power Factor	: >0.98
THD	: <10%


PRODUCT HIGHLIGHTS

- Aesthetically designed high performance pendent luminaire
- The complete luminair is made of extruded aluminium
- High efficient passive cooling extruded aluminium heat sink
- High efficiency vacuum metalized polycarbonate reflector with beam angle options of 12°, 24°, 36° & 60°
- Aesthetically designed anti glare ABS front ring
- High efficacy chip on board (COB) LED technology
- Inbuilt high efficiency electronic driver technology
- Pendent installation with wire / chain suspender and ceiling coupler
- Shade: powder coated-white, black & grey


LED PARAMETERS

WATTS	CRI	COLOR TEMP.	LUMEN	CRI	COLOR TEMP.	LUMEN
22W	90	3000 K, 3500 K, 4000 K	2289 lm, 2303 lm, 2426 lm	80	5700 K	2654 lm
24W		3000 K, 3500 K, 4000 K	2442 lm, 2513 lm, 2562 lm		5700 K	2806 lm
27W		3000 K, 3500 K, 4000 K	2634 lm, 2664 lm, 2722 lm		5700 K	3055 lm
29W		3000 K, 3500 K, 4000 K	2928 lm, 3048 lm, 3099 lm		5700 K	3275 lm
31W		3000 K, 3500 K, 4000 K	3092 lm, 3215 lm, 3279 lm		5700 K	3478 lm
35W		3000 K, 3500 K, 4000 K	3427 lm, 3561 lm, 3660 lm		5700 K	3873 lm

All dimensions are in mm




22W, 24W




27W, 29W, 31W, 35W

Color choice



Black Grey White



90 CRI 80 CRI IP20 COB



0.605

Application area for retail space:

Ambient | Entrance | Cash Counter | Stair Case