



Recess-DIFFUSED DOWN LIGHT


Wattage: 30W | 32W | 36W | 38W

## TECHNICAL SPECIFICATIONS

Light source	: MPL-Mid Power Led
Power Consumption	: 30W, 32W, 36W, 38W
80 CRI	: 3000 K   3500 K   4000 K 5700 K   6500 K
Driver	: Constant Current AC-DC
Input Voltage Range	: 220-240 V
Output Voltage	: 30V-38V DC
Output Current	: 750 mA, 800 mA, 950 mA, 1000 mA
Power Factor	: >0.95
THD	: <10%

## PRODUCT HIGHLIGHTS

- Aesthetically designed high performance surface luminaire
- The complete luminaire is made of CRCA sheet steel
- Highly efficient passive cooling deep drawn housing
- High efficiency polycarbonate symmetric light distribution diffuser
- High efficacy SMD (Mid Powder) led mounted on MCPCB for better thermal performance
- Isolated - high efficiency electronic driver fitted on the luminaire
- Heavy gauge spring toggle for easy installation on false ceiling application
- Shade : powder coated-black, white, grey



## LED PARAMETERS

WATTS	CRI	COLOR TEMP.	LUMEN
30W	80	3000 K, 3500 K, 4000 K, 5700 K, 6500 K	2730 lm, 2820 lm, 2910 lm, 3060 lm, 3150 lm
32W		3000 K, 3500 K, 4000 K, 5700 K, 6500 K	2912 lm, 3008 lm, 3104 lm, 3264 lm, 3360 lm
36W		3000 K, 3500 K, 4000 K, 5700 K, 6500 K	3276 lm, 3384 lm, 3492 lm, 3672 lm, 3780 lm
38W		3000 K, 3500 K, 4000 K, 5700 K, 6500 K	3458 lm, 3572 lm, 3572 lm, 3876 lm, 3990 lm

Color choice



Application area for retail space:  
Ambient | General Area | Trial Room | Stair case