

Pendant **HIGH-BAY DOWN LIGHT**

Wattage: 70W | 80W | 100W | 130W | 150W

TECHNICAL SPECIFICATIONS


Light source : COB-Chip on Board
 Power consumption : 70W, 80W, 100W, 130W, 150W
 90 CRI : 4000 K
 80 CRI : 5700 K
 Driver : Constant Current AC-DC
 Input voltage range : 100-240 V
 Power factor : >0.95
 THD : <15%

PRODUCT HIGHLIGHTS


- Pendant mount-down light luminaire
- Luminaire housing made out of die cast aluminium, powder coated
- Best in class LED with high levels of efficiency and colour rendering
- Efficient electronics mounted in isolated driver compartment with connectors
- Better efficiency lens for lesser transmission loss
- Good efficiency aluminium passive heat sink
- High quality reflector silver anodized aluminium
- High quality - eye bold or anchor fastener based suspension
 Beam angle : 60°, 90° & 120°
- Finished colour : Black

LED PARAMETERS

WATTS	CRI	COLOR TEMP.	LUMEN
70W	90	4000 K, 5700 K	7000 lm, 7700 lm
80W		4000 K, 5700 K	8000 lm, 8800 lm
100W		4000 K, 5700 K	10000 lm, 11000 lm
130W		4000 K, 5700 K	13000 lm, 14300 lm
150W		4000 K, 5700 K	15000 lm, 16500 lm



All dimensions are in mm



Application area for retail space:
 Factory | Warehouse