



Surface-DIFFUSED DOWN LIGHT


Wattage: 15W | 20W | 24W

TECHNICAL SPECIFICATIONS

Light source : MPL-Mid Power Led
 Power Consumption : 15W, 20W, 24W
 80 CRI : 3000 K | 3500 K | 4000 K
 5700 K | 6500 K
 Driver : Constant Current AC-DC
 Input Voltage Range : 220-240 V
 Output Voltage : 44V-74V DC
 Output Current : 250 mA, 275 mA, 300 mA
 Power Factor : >0.95
 THD : <10%

PRODUCT HIGHLIGHTS

- Aesthetically designed high performance square surface down light luminaire
- The complete luminaire is made of high grade aluminium spinning
- Highly efficient passive cooling die - cast aluminium heat sink housing
- High efficiency polycarbonate symmetric light distribution diffuser
- High efficacy SMD (Mid Powder) led mounted on MCPCB for better thermal performance
- Inbuilt-high efficiency electronic driver with suitable electrical connector
- Surface installation with ceiling clamp and accessories
- Shade : powder coated-black, white, grey



LED PARAMETERS

WATTS	CRI	COLOR TEMP.	LUMEN
15W	80	3000 K, 3500 K, 4000 K, 5700 K, 6500 K	1365 lm, 1410 lm, 1455 lm, 1530 lm, 1575 lm
20W		3000 K, 3500 K, 4000 K, 5700 K, 6500 K	1820 lm, 1880 lm, 1940 lm, 2040 lm, 2100 lm
24W		3000 K, 3500 K, 4000 K, 5700 K, 6500 K	2184 lm, 2256lm, 2328 lm, 2448 lm, 2520 lm

Color choice



Application area for retail space:
 Ambient | Trial Room | Stair Case