



IS 10322(PART 5/SEC 2):2012
R-71012963



Recess-ADJUSTABLE SPOT LIGHT

Wattage: 1X20W | 1X24W | 1X27W | 1X29W | 1X31W | 1X35W

TECHNICAL SPECIFICATIONS


Light source	: COB-Chip on Board
Power Consumption	: 1X20W, 1X24W, 1X27W, 1X29W, 1X31W, 1X35W
90 CRI	: 3000 K 3500 K 4000 K
80 CRI	: 5700 K
Driver	: Constant Current AC-DC
Input Voltage Range	: 220-240 V
Output Voltage	: 33V-37V DC
Output Current	: 600 mA, 650 mA, 700 mA 750 mA, 800 mA, 900 mA
Power Factor	: >0.95
THD	: <15%

PRODUCT HIGHLIGHTS

- Aesthetically designed high performance recess adjustable accent luminaire
- The complete luminaire housing is made of CRCA frame and die cast aluminium infill and light head
- High efficiency vacuum metalized polycarbonate reflector with beam angle options of 12°, 24°, 45° & 60°
- High efficacy chip on board (COB) LED technology
- Isolated-high efficiency electronic driver technology
- Heavy gauge spring toggle for easy installation on false ceiling application
- Shade: powder coated-white, black & grey


LED PARAMETERS

WATTS	CRI	COLOR TEMP.	LUMEN	CRI	COLOR TEMP.	LUMEN
1X20W	90	3000 K, 3500 K, 4000 K	2214 lm, 2334 lm, 2369 lm	80	5700 K	2551 lm
1X24W		3000 K, 3500 K, 4000 K	2391 lm, 2513 lm, 2562 lm		5700 K	2756 lm
1X27W		3000 K, 3500 K, 4000 K	2686 lm, 2783 lm, 2789 lm		5700 K	2979 lm
1X29W		3000 K, 3500 K, 4000 K	2887 lm, 2934 lm, 3045 lm		5700 K	3192 lm
1X31W		3000 K, 3500 K, 4000 K	3037 lm, 3084 lm, 3144 lm		5700 K	3385 lm
1X35W		3000 K, 3500 K, 4000 K	3412 lm, 3474 lm, 3528 lm		5700 K	3794 lm



Cut Sq. 165X165 mm

Color choice



Driver options



All dimensions are in mm

Application area for retail space:

Focal area | Peripheral | Show Window | Wall Display