

• Recess mount - Down light



90 CRI

PRODUCT HIGHLIGHTS


- Aesthetically designed high performance deep recess down light luminaire
- The luminaire housing is made of CRCA sheet steel with die-cast aluminium housing & ring
- High efficient passive cooling die-cast aluminium heat sink
- Secondary optics-bright anodized high efficiency anti glare aluminium reflector
- High efficiency vacuum metalized polycarbonate primary reflector with beam angle options of 12°, 24° & 40°
- High efficacy chip on board (COB) LED technology
- Isolated - high efficiency electronic driver technology
- Heavy gauge spring toggle for easy installation on false ceiling application
- Shade : powder coated - white, black & grey

Available Colours



White Black Grey

Available Reflector Deg.




IP 20

12° 24° 40°

TECHNICAL SPECIFICATIONS

Light Source	: COB - Chip on Board
Power Consumption	: 23w, 27w, 29w
Color Temperature	: 3000 K 3500 K 4000 K
Lumens	23w : 2160 lm, 2207 lm, 2119 lm 27w : 2480 lm, 2496 lm, 2529 lm 29w : 2809 lm, 2913 lm, 3025 lm
Driver	: Constant current AC - DC
Input voltage range	: 220 - 240 V
Output voltage	: 33V - 37V DC
Output Current	: 600 mA 700 mA 750 mA
Power Factor	: >0.98
THD	: <10%



Cut Dia. Ø120 mm

All dimensions are in mm

Product Application :

Retail Space | Ambient | Cash Counter | Trial Room