




Available Reflector Deg.



Recess-ADJUSTABLE SPOT LIGHT

Wattage: 22W | 24W | 27W | 29W | 31W | 35W

## TECHNICAL SPECIFICATIONS


Light source	: COB-Chip on Board
Power Consumption	: 22W, 24W, 27W, 29W, 31W, 35W
90 CRI	: 3000 K   3500 K   4000 K
80 CRI	: 5700 K
Driver	: Constant Current AC-DC
Input Voltage Range	: 220-240 V
Output Voltage	: 33V-37V DC
Output Current	: 600 mA, 650mA, 700 mA 750 mA, 800 mA, 900 mA
Power Factor	: >0.98
THD	: <10%

## PRODUCT HIGHLIGHTS

- Aesthetically designed high performance tiltable recess-spot light luminaire
- The complete luminaire is made of die-cast aluminium
- High efficient passive cooling die-cast aluminium heat sink housing
- Aesthetically designed anti glare ABS front ring
- High efficacy vacuum metalized polycarbonate reflector with beam angle options of 12°, 24°, 45° & 60°
- High efficiency chip on board (COB) LED technology
- Isolated - high efficiency electronic driver technology
- Heavy gauge spring toggle for easy installation on false ceiling application
- Shade: powder coated - white, black & grey

## LED PARAMETERS



WATTS	CRI	COLOR TEMP.	LUMEN	CRI	COLOR TEMP.	LUMEN
22W	90	3000 K, 3500 K, 4000 K	2386 lm, 2406 lm, 2471 lm	80	5700 K	2687 lm
24W		3000 K, 3500 K, 4000 K	2541 lm, 2612 lm, 2663 lm		5700 K	2865 lm
27W		3000 K, 3500 K, 4000 K	2733 lm, 2765 lm, 2823 lm		5700 K	3087 lm
29W		3000 K, 3500 K, 4000 K	2928 lm, 3048 lm, 3099 lm		5700 K	3275 lm
31W		3000 K, 3500 K, 4000 K	3092 lm, 3215 lm, 3279 lm		5700 K	3478 lm
35W		3000 K, 3500 K, 4000 K	3427 lm, 3561 lm, 3660 lm		5700 K	3873 lm



Cut Dia. Ø113 mm

All dimensions are in mm

Color choice



Driver options



Application area for retail space:

Focal area | Peripheral | Show Window | Wall Display