



Recess-ADJUSTABLE SPOT LIGHT


Wattage: 2X29W | 2X31W | 2X35W | 2X37W

TECHNICAL SPECIFICATIONS

Light source : COB-Chip on Board
 Power Consumption : 2X29W, 2X31W, 2X35W, 2X37W
 90 CRI : 3000 K | 3500 K | 4000 K
 80 CRI : 5700 K
 Driver : Constant Current AC-DC
 Input Voltage Range : 220-240 V
 Output Voltage : 33V-37V DC
 Output Current : 750 mA, 800 mA, 900 mA, 950 mA
 Power Factor : >0.98
 THD : <10%

PRODUCT HIGHLIGHTS

- Aesthetically & functionally designed high performance recess gimbal down light luminaire
- The complete luminaire housing is made of CRCA sheet steel
- High efficient passive cooling die-cast aluminium light head
- The light head individually fixed with gimbal ring to rotate 350° and tiltable 35°
- Aesthetically designed anti glare die-cast aluminium front ring
- High efficiency vacuum metalized polycarbonate reflector with beam angle options of 12°, 24°, 45° & 60°
- High efficacy chip on board (COB) LED technology
- Isolated-high efficiency electronic driver technology
- Heavy gauge clamp adjustment locking for easy installation on false ceiling application
- Shade : powder coated-white, black & grey





LED PARAMETERS

WATTS	CRI	COLOR TEMP.	LUMEN	CRI	COLOR TEMP.	LUMEN
2X29W	90	3000 K, 3500 K, 4000 K	2867 lm, 2951 lm, 2997 lm	80	5700 K	3265 lm
2X31W		3000 K, 3500 K, 4000 K	3030 lm, 3114 lm, 3266 lm		5700 K	3496 lm
2X35W		3000 K, 3500 K, 4000 K	3343 lm, 3445 lm, 3573 lm		5700 K	3875 lm
2X37W		3000 K, 3500 K, 4000 K	3497 lm, 3602 lm, 3710 lm		5700 K	4090 lm

Cut Sq.148X300 mm

Color choice



Driver options



Application area for retail space:

Focal area | Peripheral | Show Window | Wall Display