



Recess-DIFFUSED DOWN LIGHT

Wattage: 15W | 20W | 24W

## TECHNICAL SPECIFICATIONS


Light source : MPL-Mid Power Led  
 Power Consumption : 15W, 20W, 24W  
 80 CRI : 3000 K | 3500 K | 4000 K  
 5700 K | 6500 K  
 Driver : Constant Current AC-DC  
 Input Voltage Range : 220-240 V  
 Output Voltage : 44V-74V DC  
 Output Current : 250 mA, 275 mA, 300 mA  
 Power Factor : >0.95  
 THD : <10%

## PRODUCT HIGHLIGHTS

- Aesthetically designed high performance circular recess down light luminaire
- The complete luminaire is made of die cast aluminium
- Highly efficient passive cooling die-cast aluminium heat sink housing
- High efficiency polycarbonate symmetric light distribution diffuser
- High efficacy SMD (Mid Powder) led mounted on MCPCB for better thermal performance
- Isolated-high efficiency electronic driver with suitable electrical connector
- Heavy gauge spring toggle for easy installation on false ceiling application
- Shade: powder coated-black, white, grey



Cut Dia. Ø125 mm  
15W



Cut Dia. Ø150 mm  
20W

Cut Dia. Ø175 mm  
24W

## LED PARAMETERS

WATTS	CRI	COLOR TEMP.	LUMEN
15W	80	3000 K, 3500 K, 4000 K, 5700 K, 6500 K	1365 lm, 1410 lm, 1455 lm, 1530 lm, 1575 lm
20W		3000 K, 3500 K, 4000 K, 5700 K, 6500 K	1820 lm, 1880 lm, 1940 lm, 2040 lm, 2100 lm
24W		3000 K, 3500 K, 4000 K, 5700 K, 6500 K	2184 lm, 2256lm, 2328 lm, 2448 lm, 2520 lm

Color choice



Application area for retail space:  
Ambient | Trial Room | Stair case