

Pendant **HIGH-BAY DOWN LIGHT**

Wattage : 50W | 100W | 150W | 200W

TECHNICAL SPECIFICATIONS


Light source : COB-Chip on Board
 Power consumption : 50W, 100W, 150W, 200W
 80 CRI : 3000 K, 3500 K, 4000 K, 5700 K
 Driver : Constant Current AC-DC
 Input voltage range : 100-240 V
 Power factor : >0.95
 THD : <15%

PRODUCT HIGHLIGHTS


- Pendant / Surface mounted-high bay luminaire
- Luminaire housing made out of die cast aluminium, powder coated
- High efficacy SMD LED-higher lm/W and good colour rendering
- Efficient electronic driver mounted in isolated compartment with connectors
- High efficiency lens for lesser transmission loss
- Good efficiency aluminium passive heat sink
- Beam angle : 90°,120°
- Finished colour : Black

LED PARAMETERS

WATTS	CRI	COLOR TEMP.	LUMEN
50W	80	3000 K, 3500 K, 4000 K, 5700 K	4800 lm, 4950 lm, 5150 lm, 5600 lm
100W		3000 K, 3500 K, 4000 K, 5700 K	9600 lm, 9900 lm, 10100 lm, 11300 lm
150W		3000 K, 3500 K, 4000 K, 5700 K	14550 lm, 14850 lm, 15300 lm, 16650 lm
200W		3000 K, 3500 K, 4000 K, 5700 K	19380 lm, 19600 lm, 20400 lm, 22400 lm



All dimensions are in mm



Application area for retail space:
 Factory | Warehouse