

• Recess mount - Down light



90 CRI

## PRODUCT HIGHLIGHTS

- Aesthetically designed high performance recess asymmetric down light luminaire
- The luminaire housing is made of CRCA sheet steel with die-cast aluminium ring
- High efficient passive cooling-extruded aluminium heat sink
- High efficiency vacuum metalized polycarbonate asymmetric reflector for wall washer application
- High efficacy chip on board (COB) LED technology
- Isolated - high efficiency electronic driver technology
- Heavy gauge spring toggle for easy installation on false ceiling application
- Shade : powder coated - white, black & grey

Available Colours




## TECHNICAL SPECIFICATIONS

Light Source	: COB - Chip on Board
Power Consumption	: 29w, 32w, 35w
Color Temperature	: 3000 K   3500 K   4000 K
Lumens	29w : 2809 lm, 2913 lm, 3025 lm
	32w : 2943 lm, 3143 lm, 3159 lm
	35w : 3243 lm, 3425 lm, 3455 lm
Driver	: Constant current AC - DC
Input voltage range	: 220 - 240 V
Output voltage	: 33V - 37V DC
Output Current	: 750 mA   800 mA   900 mA
Power Factor	: >0.98
THD	: <10%



Cut Dia. Ø130 mm



All dimensions are in mm

**Product Application :**  
Retail Space | Ambient | Cash Counter | Trial Room