

# DELLA HD-II-INNOVA





Wattage : 2X29W | 2X31W | 2X35W | 2X37W

## PRODUCT HIGHLIGHTS

- Aesthetically & functionally designed high performance recess down light luminaire
- The complete luminaire housing is made of CRCA sheet steel
- High efficient passive cooling die-cast aluminium light head
- The light head individually rotatable 350° and tiltable 35°
- Aesthetically designed anti glare die-cast aluminium front ring
- High efficiency vacuum metalized polycarbonate reflector with beam angle options of 12°, 24°, 45° & 60°
- High efficacy chip on board (COB) LED technology
- Isolated-high efficiency electronic driver technology
- Heavy gauge clamp adjustment locking for easy installation on false ceiling application
- Shade: powder coated-white, black & grey

## LED PARAMETERS

WATTS	CRI	COLOR TEMP.	LUMEN	CRI	COLOR TEMP.	LUMEN
2X29W		3000 K, 3500 K, 4000 K	2867 lm, 2951 lm, 2997 lm		5700 K	3265 lm
2X31W		3000 K, 3500 K, 4000 K	3030 lm, 3114 lm, 3266 lm		5700 K	3496 lm
2X35W	90	3000 K, 3500 K, 4000 K	3343 lm, 3445 lm, 3573 lm	80	5700 K	3875 lm
2X37W		3000 K, 3500 K, 4000 K	3497 lm, 3602 lm, 3710 lm		5700 K	4090 lm



Cut Sq. 151X270 mm

All dimensions are in mm

# DELLA HD-I-INNOVA

GARDLER®



Wattage : 1X29W | 1X31W | 1X35W | 1X37W



Recess-ADJUSTABLE SPOT LIGHT



## TECHNICAL SPECIFICATIONS

Light Source	: COB-Chip on Board
Power Consumption	: 1x29W, 1x31W, 1x35W, 1x37W
90 CRI	: 3000 K   3500 K   4000 K
80 CRI	: 5700 K

Driver	: Constant Current AC-DC
Input Voltage Range	: 220-240 V
Output Voltage	: 33V-37V DC
Output Current	: 750 mA, 800 mA, 900 mA, 950 mA
Power Factor	: >0.98
THD	: <10%

## LED PARAMETERS

WATTS	CRI	COLOR TEMP.	LUMEN	CRI	COLOR TEMP.	LUMEN
1X29W		3000 K, 3500 K, 4000 K	2867 lm, 2951 lm, 2997 lm		5700 K	3265 lm
1X31W		3000 K, 3500 K, 4000 K	3030 lm, 3114 lm, 3266 lm		5700 K	3496 lm
1X35W	90	3000 K, 3500 K, 4000 K	3343 lm, 3445 lm, 3573 lm	80	5700 K	3875 lm
1X37W		3000 K, 3500 K, 4000 K	3497 lm, 3602 lm, 3710 lm		5700 K	4090 lm



Cut Sq. 151X151 mm

Color choice:  Black  Grey  White

Driver options:  90 CRI  80 CRI  IP20  COB  DALI  Tunable

Application area for retail space:  
Focal area | Peripheral | Show Window | Wall Display