

Power Track-ACCENT LIGHT

Wattage: 31W | 35W

TECHNICAL SPECIFICATIONS

Light Source	: COB-Chip on Board
Power Consumption	: 31W, 35W
90 CRI	: 3000 K 3500 K 4000 K
80 CRI	: 5700 K
Driver	: Constant current AC-DC
Input Voltage Range	: 220-240 V
Output Voltage	: 33V-37V DC
Output Current	: 800 mA, 900mA
Power Factor	: >0.95
THD	: <15%


PRODUCT HIGHLIGHTS

- Aesthetically designed cylindrical power track mounted-accent luminaire
- Specially engineered 355° rotatable luminaire and 45°-90° adjustable light head
- The complete luminaire is made of extruded aluminium
- High efficient passive cooling extruded aluminium light head
- Aesthetically designed anti glare ABS front ring
- High efficiency vacuum metalized polycarbonate reflector with beam angle options of 12°, 24°, 45° & 60°
- High efficacy chip on board (COB) LED technology
- Adaptor based inbuilt high efficiency electronic driver technology
- Adaptor-suitable for 3 wire / 4 wire power track
- Shade : powder coated-white, black & grey

3 | 4 CKT

LED PARAMETERS

WATTS	CRI	COLOR TEMP.	LUMEN	CRI	COLOR TEMP.	LUMEN
31W	90	3000 K, 3500 K, 4000 K	3067 lm, 3211 lm, 3225 lm	80	5700 K	3380 lm
35W		3000 K, 3500 K, 4000 K	3384 lm, 3532 lm, 3578 lm		5700 K	3710 lm



All dimensions are in mm

Color choice



Application area for retail space:
Focal area | Ambient | Show Window | Wall Display