

DOLPH-ADSA-3C



IS 10322(PART 5/SEC 1):2012
R-71007862

Wattage: 23W | 27W


PRODUCT HIGHLIGHTS

- Aesthetically designed compact power track mounted-accent luminaire
- Specially engineered 355° rotatable luminaire and 45°-90° adjustable light head
- The complete luminaire is made of die-cast aluminium
- High efficient passive cooling die-cast aluminium light head with rotatable arm
- Aesthetically designed anti glare ABS front ring
- High efficiency vacuum metalized polycarbonate reflector with beam angle options of 16°, 24° & 40°
- High efficacy chip on board (COB) LED technology
- Adaptor based inbuilt high efficiency electronic driver technology
- Adaptor-suitable for 3 wire power track
- Shade: powder coated-black, white & grey

3 CKT

LED PARAMETERS

WATTS	CRI	COLOR TEMP.	LUMEN	CRI	COLOR TEMP.	LUMEN
23W	90	3000 K, 3500 K, 4000 K	2003 lm, 2025 lm, 2058 lm	80	5700 K	2363 lm
27W		3000 K, 3500 K, 4000 K	2340 lm, 2367 lm, 2408 lm		5700 K	2744 lm



Application area for retail space:
Focal area | Ambient | Show Window | Wall Display

DOLPH-ADSA-4C

GARDLER®



IS 10322(PART 5/SEC 1):2012
R-71007862

Power Track-ACCENT LIGHT

Wattage: 15W | 17W | 19W | 23W | 25W | 27W | 29W



TECHNICAL SPECIFICATIONS

Light Source : COB-Chip on Board
Power Consumption : 15W, 17W, 19W, 23W, 25W, 27W, 29W


90 CRI : 3000 K | 3500 K | 4000 K
80 CRI : 5700 K

Driver : Constant current AC-DC
Input Voltage Range : 220-240 V
Output Voltage : 33V-37V DC
Output Current : 400 mA, 450 mA, 500 mA, 600 mA, 650 mA, 700 mA, 750 mA

Power Factor : >0.95
THD : <15%

4 CKT

WATTS	CRI	COLOR TEMP.	LUMEN	CRI	COLOR TEMP.	LUMEN
15W	90	3000 K, 3500 K, 4000 K	1334 lm 1349 lm 1370 lm	80	5700 K	1581 lm
17W		3000 K, 3500 K, 4000 K	1565 lm 1582 lm 1600 lm		5700 K	1840 lm
19W		3000 K, 3500 K, 4000 K	1710 lm 1729 lm 1748 lm		5700 K	2014 lm
23W		3000 K, 3500 K, 4000 K	2003 lm 2025 lm 2058 lm		5700 K	2363 lm
25W		3000 K, 3500 K, 4000 K	2140 lm 2165 lm 2213 lm		5700 K	2558 lm
27W		3000 K, 3500 K, 4000 K	2340 lm 2367 lm 2408 lm		5700 K	2744 lm
29W		3000 K, 3500 K, 4000 K	2448 lm 2477 lm 2508 lm		5700 K	2909 lm



All dimensions are in mm